

MEETING YOUR DEMANDS

High- & Low Speed Handpieces
Prophylaxis | Motors | Quick Connectors
Replacement Cartridges & Spare Parts
Turbings | Tools & Lubrication



Your Powerful Partner

CLASSIC LINE HC20KL **28 W**

The Silent Match

PRIME LINE HP21KL **55 dB**



The Silent Match

PRIME LINE HP21KL **55 dB**

THE PRIME LINE

The PRIME LINE spindle has a two-part bur guide with a carbide insert for the highest level of concentricity and resistance to bending. With over 40 N of retention force, the spindle guarantees that the bur is securely held.

The vibration-free running results in a sound level of less than 55 dB at powerful 25W. This makes the PRIME LINE quiet like no other (HP21KL).


FEATURES

- Prime Grip
- Non-return valves
- Pushbutton system

- Titanium coating
- Glass rod light conductor
- Ceramic bearings

- Premium spindle with carbide insert

- Pressure reduction system (only KaVo MULTiflex®)



HP21KL High Speed Handpiece

Standard head with light
25 W
4-hole spray
KaVo MULTiflex® connection

HP21NL High Speed Handpiece

Standard head with light
25 W
4-hole spray
NSK Phatelus® connection

HP21WL High Speed Handpiece

Standard head with light
25 W
4-hole spray
W&H Roto Quick® connection

HP21SL High Speed Handpiece

Standard head with light
25 W
4-hole spray
Sirona® connection



HP22KL High Speed Handpiece

Small head with light
18 W
3-hole spray
KaVo MULTiflex® connection

HP22NL High Speed Handpiece

Small head with light
18 W
3-hole spray
NSK Phatelus® connection

HP22WL High Speed Handpiece

Small head with light
18 W
3-hole spray
W&H® connection





Your Powerful Partner

CLASSIC LINE HC20KL **28 W**

THE CLASSIC LINE



One result of our research is the newly designed grip for the CLASSIC LINE. The Classic Grip fits perfectly in your hand. Tangibly improved ergonomics and higher stability are the results. A high resistance to wearout and corrosion is ensured through the high quality coating of the surface. Another great part of the CLASSIC LINE: The Power Edition! 28 W Power built in a standard head, available with and without light.

FEATURES

- Classic Grip
- Pushbutton system

- Chrome coating
- Ceramic bearings

- Premium spindle with carbide insert
- Glass rod light conductor



HC20 - POWER EDITION

High Speed Handpiece

Standard head with or without light
28 W
4-hole spray
KaVo MULTIflex® connection

Available with following options:

With light (HC20KL)
Without light (HC20K)



HC21

High Speed Handpiece

Standard head with or without light
23 W
4-hole spray
KaVo MULTIflex® connection

Available with following options:

With light (HC21KL)
Without light (HC21K)



HC22

High Speed Handpiece

Small head with or without light
18 W
3-hole spray
KaVo MULTIflex® connection

Available with following options:

With light (HC22KL)
Without light (HC22K)

THE ECO LINE SERIES

High Flexibility, low Price!

FEATURES

- Smooth Grip
- Pushbutton system
- Chrome coating
- Ceramic bearings
- Premium spindle with steel insert
- Glass rod light conductor



HE21

High Speed Handpiece

Standard head with or without light
21 W
4-hole spray

Available with following options:

KaVo MULTIflex® connection (HE21KL | HE21K)
NSK Phatelus/Mach® connection (HE21NL | HE21N)
W&H Roto Quick® connection (HE21WL | HE21W)
Sirona® connection (HE21SL | HE21S)



HE22

High Speed Handpiece

Small head with or without light
16 W
3-hole spray

Available with following connections:

KaVo MULTIflex® connection (HE22KL | HE22K)
NSK Phatelus/Mach® connection (HE22NL | HE22N)
W&H Roto Quick® connection (HE22WL | HE22W)



HIGH SPEED HANDPIECES WITH TUBING CONNECTION



HE11
High Speed Handpiece

Standard head
18 W
1-hole spray
2-hole connection



HE12
High Speed Handpiece

Standard head
18 W
1-hole spray
4-hole connection



HE14
High Speed Handpiece

Mini head
15 W
1-hole spray
4-hole connection



HE17
High Speed Handpiece

Standard head
18 W
4-hole spray
4-hole connection



HE18
High Speed Handpiece

Small head
16 W
3-hole spray
4-hole connection

THE BASIC LINE SERIES

Proven Technology, safe Grip!

FEATURES

- Basic Grip
- Pushbutton system
- Chrome coating
- Ceramic bearings
- Premium spindle with steel insert
- Glass rod light conductor



HB21 High Speed Handpiece

Standard head with or without light
21 W
4-hole spray
KaVo MULTIflex® connection

Available with following options:
With light (HB21KL)
Without light (HB21K)



HB23 High Speed Handpiece

Mini head with or without light
15 W
1-hole spray
KaVo MULTIflex® connection

Available with following options:
With light (HB23KL)
Without light (HB23K)



HB12 High Speed Handpiece

Standard head
18 W
1-hole spray
4-hole connection



HB14 High Speed Handpiece

Mini head
15 W
1-hole spray
4-hole connection

EFFICIENT INTERFACE

Quick & Flexible Connection!

QUICK CONNECTORS FOR HIGH SPEED HANDPIECES



6-hole Quick Connector

With spray regulation system
MK-dent & KaVo MULTiflex® connection

Available in the following versions:
QC6016KW with LED
QC5016KW with Xenon



6-hole Quick Connector

MK-dent & KaVo MULTiflex® connection

Available in the following versions:
QC6016K with LED
QC5016K with Xenon



Quick Connector

MK-dent & KaVo MULTiflex® connection

Available in the following versions:
QC4014K without light (4-hole)
QC4012K without light (2-hole)



6-hole Quick Connector

With spray regulation system
Sirona® connection

Available in the following versions:
QC6016SW with LED
QC5016SW with Xenon



Quick Connector

W&H Roto Quick® connection

Available in the following versions:
QC5016W with power supply (6-hole)
QC4014W without power supply (4-hole)



Quick Connector

NSK MachLite® connection

Available in the following versions:
QC6016NT with LED (6-hole)
QC5016NT with Xenon (6-hole)
QC4014NT without light (4-hole)



THE PRIME LINE SERIES

Operating Convenience!

The combination of a brushed stainless steel housing and a titanium coating offers a perfect grip, protection against corrosion and maximum scratch resistance. Due to the ideal angle combination, you can treat hard to reach preparation areas for maximum comfort during treatment.

CONTRA ANGLE HEADS

FEATURES

- KaVo® compatible
- Titanium coating
- Pushbutton system



LPH11
Contra Angle Head

1:1, blue
Max. 40.000 rpm
For CA-burs (Ø 2,35 mm)



LPH16
Contra Angle Head

1:1, blue
Max. 40.000 rpm
For FG-burs (Ø 1,6 mm)



LPH21
Contra Angle Head

2:1, green
Max. 20.000 rpm
For CA-burs (Ø 2,35 mm)

STRAIGHT HANDPIECES & CONTRA ANGLE BODIES

FEATURES

- Prime Grip
- With light
- INTRAmatic® connection
- Stainless steel case with titanium coating



LP01L
Straight Handpiece with light

1:1, blue
With internal water
Max. 40.000 rpm
For HP-burs (Ø 2,35 mm)



LP11L
Contra Angle Body with light

1:1, blue
With internal water
Max. 40.000 rpm
For MK-dent and KaVo® heads



LP27L
Contra Angle Body with light

2,7:1, green
With internal water
Max. 14.814 rpm
For MK-dent and KaVo® heads



LP74L
Contra Angle Body with light

7,4:1, green
With internal water
Max. 5.406 rpm
For MK-dent and KaVo® heads



THE CLASSIC LINE SERIES

Feel the Advantage!

The Classic Grip fits perfectly in your hand. Tangibly improved ergonomics and higher stability are the results. A high resistance to wear and corrosion is ensured through the high quality chrome coating of the surface and the brass housing.

CONTRA ANGLE HEADS

FEATURES

- KaVo® compatible
- Chrome coating
- Pushbutton system



LCH11
Contra Angle Head

1:1, blue
Max. 40.000 rpm
For CA-burs (Ø 2,35 mm)



LCH16
Contra Angle Head

1:1, blue
Max. 40.000 rpm
For FG-burs (Ø 1,6 mm)



LCH21
Contra Angle Head

2:1, green
Max. 20.000 rpm
For CA-burs (Ø 2,35 mm)



LCH21P
Contra Angle Head

2:1, green
Max. 20.000 rpm
For snap-on and screw-in
prophy attachments



STRAIGHT HANDPIECES & CONTRA ANGLE BODIES

FEATURES

- Classic Grip
- Chrome coating
- With or without light
- INTRAmatic® connection



LC01L / LC01
Straight Handpiece with / without light

1:1, blue
With internal water
Max. 40.000 rpm
For HP-burs (Ø 2,35 mm)



LC11L / LC11
Contra Angle Body with / without light

1:1, blue
With internal water
Max. 40.000 rpm
For MK-dent and KaVo® heads



LC27L / LC27
Contra Angle Body with / without light

2,7:1, green
With internal water
Max. 14.814 rpm
For MK-dent and KaVo® heads



LC74L / LC74
Contra Angle Body with / without light

7,4:1, green
With internal water
Max. 5.406 rpm
For MK-dent and KaVo® heads

THE ECO LINE SERIES

Solid Performance!

The ECO LINE Contra Angle Handpieces with built-in contra angle head offer high-tech precision and convincing reliability for a nice price.

The wide spectrum of transmissions provides the right handpiece for each purpose.



STRAIGHT- & CONTRA ANGLE HANDPIECES

FEATURES

- Smooth Grip
- Chrome coating
- With or without light
- Pushbutton system
- INTRAmatic® connection



LE01L / LE01

Straight Handpiece with / without light

1:1, blue
With internal water
Max. 40.000 rpm
For HP-burs (Ø 2,35 mm)



LE11L / LE11

Contra Angle Handpiece with / without light

1:1, blue
With internal water
Max. 40.000 rpm
For CA-burs (Ø 2,35 mm)



LE16L / LE16

Contra Angle Handpiece with / without light

1:1, blue
With internal water
Max. 40.000 rpm
For FG-burs (Ø 1,6 mm)



LE21L / LE21

Contra Angle Handpiece with / without light

2:1, green
With internal water
Max. 20.000 rpm
For CA-burs (Ø 2,35 mm)



LE27L / LE27

Contra Angle Handpiece with / without light

2,7:1, green
With internal water
Max. 14.814 rpm
For CA-burs (Ø 2,35 mm)



LE54L / LE54

Contra Angle Handpiece with / without light

5,4:1, green
With internal water
Max. 7.407 rpm
For CA-burs (Ø 2,35 mm)



LE54PL / LE54P

Contra Angle Handpiece with / without light

5,4:1, green
With internal water
Max. 7.407 rpm
For snap-on and screw-in prophy attachments



LE74L / LE74

Contra Angle Handpiece with / without light

7,4:1, green
With internal water
Max. 5.406 rpm
For CA-burs (Ø 2,35 mm)



LE148L / LE148

Contra Angle Handpiece with / without light

14,8:1, green
With internal water
Max. 2.703 rpm
For CA-burs (Ø 2,35 mm)



THE BASIC LINE SERIES

Proven Technology, Save Grip!

The Basic Grip guarantees a safe and comfortable feeling at work – in all situations. The chrome coating is particularly resistant and easy to clean.

Also, on a selection of BASIC LINE straight- and contra angle handpieces, you have the choice between external water or no water supply.

CONTRA ANGLE HEADS

FEATURES

- Chrome coating
- NSK® EX series compatible



LBH11
Contra Angle Head

1:1, blue
Max. 20.000 rpm
Pushbutton system
For CA-burs (Ø 2,35 mm)



LBH11P
Contra Angle Head

1:1, blue
Max. 5.000 rpm
For snap-on prophy cups



LBH11C
Contra Angle Head

1:1, blue
Max. 20.000 rpm
Latch type system
For CA-burs (Ø 2,35 mm)

STRAIGHT- & CONTRA ANGLE HANDPIECES

FEATURES

• Basic Grip

• Chrome coating

• INTRAMatic® connection



LB01

Straight Handpiece

1:1, blue
Max. 20.000 rpm
For HP burs (Ø 2,35 mm)
INTRAMatic® connection



LB02

Straight Handpiece

1:1, blue
External water via clip-on hose
Max. 20.000 rpm
For HP burs (Ø 2,35 mm) and
disposable prophylactic heads
INTRAMatic® connection



LB11/11

Contra Angle Handpiece

1:1, blue
External water via clip-on hose
Max. 20.000 rpm
For CA-burs (Ø 2,35 mm)
INTRAMatic® connection



LB11/11C

Contra Angle Handpiece

1:1, blue
External water via clip-on hose
Max. 20.000 rpm
For CA-burs (Ø 2,35 mm)
INTRAMatic® connection



LB41/11

Contra Angle Handpiece

4:1, green
External water via clip-on hose
Max. 5.000 rpm
For CA-burs (Ø 2,35 mm)
INTRAMatic® connection



LB41/11P

Contra Angle Handpiece

4:1, green
Max. 5.000 rpm
For snap-on prophylactic cups
INTRAMatic® connection

FOR STRAIGHT & CONTRA ANGLE HANDPIECES

Powerful Drive!

ELECTRIC MOTOR



EM1190K
Electric Motor with LED

- Max. 40.000 rpm
- Spray regulation system
- Guided interior separate coolants
- Short INTRAmatic® 2 connection, suitable for all common instruments
- Compatible with KaVo® 190, 196 and K200 connections

AIRMOTORS WITH INTERNAL WATER



AM1116
6-hole Airmotor with LED

- Titanium coating
- Max. 20.000 rpm
- Internal water supply
- Infinitely adjustable right and left drive
- Spray regulation system
- Guided interior separate coolants
- Standard INTRAmatic® connection, suitable for all common instruments



AM1004
4-hole Airmotor

- Max. 20.000 rpm
- Internal water supply
- Infinitely adjustable right and left drive
- Guided interior separate coolants
- Standard INTRAmatic® connection, suitable for all common instruments

AIRMOTORS WITH EXTERNAL WATER AND WITHOUT WATER



AM0014
4-hole Airmotor

- Max. 20.000 rpm
- External clip-on water supply
- Standard INTRAmatic® connection, suitable for all common instruments

Available with following option:
With 2-hole connection (AM0012)



AM0004
4-hole Airmotor

- Max. 20.000 rpm
- Without water supply
- Standard INTRAmatic® connection, suitable for all common instruments

Available with following option:
With 2-hole connection (AM0002)

PREMIUM SERVICE OIL

Optimum Care!

Full synthetic Premium Service Oil, 500ml

For maintenance of high and low speed handpieces, airmotors and air flow handpieces. With mint scent.

Available in the following versions:

For a large selection of lubrication tools for many brands (LU1011)

For the KaVo® Quattrocare 2 system (LU1022)

For the W&H® Assistina and other maintenance units (LU1031)



ALUMINIUM LUBRICATION TOOLS



LT1011



LT1012



LT1013



LT1014

Suitable for	High speed handpieces with MK-dent connection	High speed handpieces with KaVo® connection	Low speed handpieces with INTRAmatic® connection	FG and PB spindles, Ø 1,6 mm
--------------	---	---	--	------------------------------



LT1015



LT1017



LT1018



LT1019

Suitable for	4-hole and 5-hole connections	High speed handpieces with Sirona® connection	Handpieces with W&H® connection	Handpieces with NSK® connection (CHQD)
--------------	-------------------------------	---	---------------------------------	--



LT1020



LT1021



LT1022

Suitable for	Handpieces with NSK® connection (Ti-Max)	High speed handpieces with Star® connection	Handpieces with Yoshida® connection
--------------	--	---	-------------------------------------



ULTRASONIC SCALER

Perfect Cleaning!

ULTRASONIC SCALER

FEATURES

- Ergonomic shape for excellent grip
- Painfree treatments for the patient through linear movements of the tip
- Lean steel sleeve for a long durability
- 6-LED light ring for optimum lighting
- Available for the following connections: KaVo® | EMS® | Acteon-Satelec®



SC21E

Scaler Handpiece

24 – 33 kHz
Steel funnel cover
EMS® connection, type EN-041



SC21E2

Scaler Handpiece

24 – 33 kHz
Steel funnel cover
EMS® connection, type EN-061



SC21EL

Scaler Handpiece with light

24 – 33 kHz
Steel funnel cover
EMS® connection, type EN-060A



SC21KL*

Scaler Handpiece with light

24 – 33 kHz
Steel funnel cover
KaVo® connection,
REF 1.007.3995



SC21S

Scaler Handpiece

24 – 33 kHz
Steel funnel cover
Acteon-Satelec® connection,
type F 12 281



SC21SL

Scaler Handpiece with light

24 – 33 kHz
Steel funnel cover
Acteon-Satelec® connection,
type F 12 609

* Only for use with MK-dent STxxE/ED or EMS® original scalertips.

THE INNOVATIVE DLC COATING TECHNIQUE

Diamond-like Carbon!

SCALERTIP FEATURES

- High quality DLC coating
- Extreme hard and wear resistant, for an up to 40% longer lifetime
- Optimum view through a reflection-poor surface
- Anti-allergenic

Art. No EMS® Satelec®	ST01E ST01S		ST01ED ST01SD		ST02E ST02S		ST02ED ST02SD	
Application area	Scaling		Scaling		Scaling		Scaling	
Coating/Material	Stainless steel		DLC		Stainless steel		DLC	
Art. No EMS® Satelec®	ST03E ST03S		ST03ED ST03SD		ST04E ST04S		ST04ED ST04SD	
Application area	Scaling		Scaling		Scaling		Scaling	
Coating/Material	Stainless steel		DLC		Stainless steel		DLC	
Art. No EMS® Satelec®	ST05E ST05S		ST06E ST06S		ST06ED ST06SD		ST07E ST07S	
Application area	Endodontics		Periodontal		Periodontal		Periodontal	
Coating/Material	Stainless steel		Stainless steel		DLC		Stainless steel	
Art. No EMS® Satelec®	ST08E ST08S		ST08ED ST08SD		ST09E ST09S		ST10E ST10S	
Application area	Periodontal		Periodontal		Periodontal		Periodontal	
Coating/Material	Stainless steel		DLC		Stainless steel		Stainless steel	
Art. No EMS® Satelec®	ST10ED ST10SD		ST11E ST11S		ST12E ST12S		ST13E ST13S	
Application area	Periodontal		Periodontal		Endodontics		Endodontics	
Coating/Material	DLC		Stainless steel		Stainless steel		Stainless steel	
Art. No EMS® Satelec®	ST14E ST14S		ST15E ST15S		ST16E ST16S		ST17E ST17S	
Application area	Endodontics		Endodontics		Endodontics		Endodontics	
Coating/Material	Stainless steel		Stainless steel		Stainless steel		Stainless steel	
Art. No EMS® Satelec®	ST18E ST18S		ST19E ST19S		ST20E ST20S		ST21E ST21S	
Application area	Endodontics		Cavity preparation		Cavity preparation		Cavity preparation	
Coating/Material	Stainless steel		Stainless steel		Stainless steel		Stainless steel	
Art. No EMS® Satelec®	ST22E ST22S		ST23E ST23S					
Application area	Cavity preparation		Cavity preparation					
Coating/Material	Stainless steel		Stainless steel					

SC22KEY Endo Torque

Endo key for a safe attachment of Endotips.

SC21KEY Torque Key

Torque wrench for correct mounting and holder for safe sterilization and storage of the scaler tips.





THE PROPHY LINE SERIES

Efficient & Universal!

AIR POLISHING DEVICE

FEATURES

- Ergonomically shaped and compact
- 360° rotatable outer handle RotoGrip®- system for simple and fatigue proof operation

PR1011

Air Polishing Device

Universal and compact polishing device for gentle prophylaxis treatments.

Available with the following connections:

- KaVo® connection (PR1011K)
- W&H® connection (PR1011W)
- Sirona® connection (PR1011S)
- NSK® connection (PR1011N)
- Bien-Air® connection (PR1011B)



Prophylaxis Cleaning Powder

For Prophyl Line and air polishing devices. Extra fine grain size: 12 - 14 µm.

Available in the following flavors:

- Mint flavor (PP1011)
- Lemon flavor (PP1012)
- Strawberry flavor (PP1013)

LED ULTRA HIGH BRILLIANCE!



FEATURES

- Excellent brilliance, no glare or haloes
- 5500 K daylight color temperature, very eye-friendly
- Flexible, user-friendly and economic
- 15 times longer durability compared to other halogen and Xenon illuminants
- Available for the following brands: KaVo® | W&H® | Sirona® | NSK® | Bien-Air® | Castellini® | Star® | Faro® | Yoshida® | Midwest®

BU8012	For MK-dent and KaVo® quick connectors
BU8012KM	For MK-dent AM1016 and KaVo® motors
BU8012EM	For MK-dent EM1190K
BU8012SB	For Sirona® quick connectors, SPRAYVIT L tubings and Sirosonic L scaler
BU8012SG	For Sirona® motors
BU8012BA	For Bien-Air® motors (not for rotating current)
BU8012BA/V2*	For Bien-Air® motors (not for rotating current)
BU8012BAK	For Bien-Air® quick connectors and high speed handpieces, Midwest® 6-Pin quick connectors
BU8012WH	For W&H® high speed handpieces
BU8012WH/V2*	For W&H® high speed handpieces
BU8012WLT	For W&H® airmotors LT25
BU8012WEA	For W&H® motors 40LT, 50LT and A51LT
BU8012WRA	For W&H® quick connectors RA24
BU8012WRA/V2*	For W&H® quick connectors RA24
BU8012N	For NSK® quick connectors
BU8012NT	For NSK® motors TIM40 and TI205L
BU8012NNL	For NSK® NL motors
BU8012NM	For NSK® motors Ti-Max M40 LED, M205LG, NBS, X205L and quick connectors KCL, SCL, PTL LED
BU8012C	For Castellini® high speed handpieces
BU8012C/V2*	For Castellini® high speed handpieces
BU8012ST	For Star® quick connectors
BU8012ST/V2*	For Star® quick connectors
BU8012F	For Faro® high speed handpieces
BU8012Y	For Yoshida® quick connectors

* V2 - LEDs with reversed polarity

Xenon HIGH LUMINOSITY, GREAT PRICE!

FEATURES

- High luminosity
- Precise illuminance
- Long durability
- Available for the following brands: KaVo® | W&H® | Sirona® | NSK® | Bien-Air® | Star®



BU7012	For MK-dent and KaVo® quick connectors and motors
BU7012SB	For Sirona® quick connectors, SPRAYVIT L tubings and Sirosonic L scaler
BU7012SG	For Sirona® motors
BU7012WH	For W&H® high speed handpieces
BU7012BA	For Bien-Air® motors
BU7012BAK	For Bien-Air® high speed handpieces
BU7012N	For NSK® quick connectors
BU7012ST	For Star® quick connectors

REPLACEMENT CARTRIDGES

Breathtaking Performance!



CHOOSE BETWEEN THREE QUALITIES:

- Premium Cartridge
Carbide insert with ceramic bearings
- Standard Cartridge
Steel insert with ceramic bearings
- Basic Cartridge
Steel insert with steel bearings

Your Turbine	Suitable Premium Cartridge	Suitable Standard Cartridge	Suitable Basic Cartridge
MK-dent			
HB12	TC2021	TC1021	-
HB14	TC2033	TC1033	-
HB15L	TC2021	TC1021	-
HB16L	-	TC1033	-
HB21K/KL	TC2034	TC1034	-
HB23K/KL	TC2033	TC1033	-
HC20K/KL	TC2038	-	-
HC21K/KL	TC2038	-	-
HC22K/KL	TC2039	-	-
HE11	TC2021	TC1021	-
HE12	TC2021	TC1021	-
HE14	TC2035	TC1035	-
HE15L	TC2021	TC1021	-
HE16L	TC2035	TC1035	-
HE17	TC2034	TC1034	-
HE18	TC2035	TC1035	-
HE21K/KL/N/NL/W/WL/S/SL	TC2034	TC1034	-
HE22K/KL/N/NL/W/WL	TC2035	TC1035	-
HP21KL/NL/WL/SL	TC2041	-	-
HP22KL/NL/WL	TC2042	-	-
KaVo®			
4500B/BR	TC2500BK	TC1500BK	TS1500BK
5000B/BY	TC2500BK	TC1500BK	TS1500BK
6000B	TC2600BK	TC1600BK	TS1600BK
630B/C	TC2640BK	TC1640BK	TS1640BK
632D/E/EA	TC2642BK	TC1642BK	TS1642BK
635B	TC2635BK	TC1635BK	TS1635BK
635BR	TC2637BK	TC1635BK	TS1635BK
636CP/P	TC2636BK	TC1636BK	TS1636BK
637B/C	TC2637BK	TC1637BK	TS1637BK
639B/C	TC2642BK	TC1642BK	TS1642BK
640B/C	TC2640BK	TC1640BK	TS1640BK
642B/C	TC2642BK	TC1642BK	TS1642BK
645B/C	TC2642BK	TC1642BK	TS1642BK
646B/C	TC2642BK	TC1642BK	TS1642BK

Your Turbine	Suitable Premium Cartridge	Suitable Standard Cartridge	Suitable Basic Cartridge
KaVo®			
647B	TC2647BK	TC1647BK	TS1647BK
649B	TC2647BK	TC1647BK	TS1647BK
6500B	TC2650US	TC1650US	TS1650US
6500BR	TC2800BK	TC1800BK	TS1800BK
650B	TC2650BK	TC1650BK	TS1650BK
655B/C	TC2655BK	TC1655BK	TS1655BK
659BR	TC2655BK	TC1655BK	TS1655BK
660B/C	TC2655BK	TC1655BK	TS1655BK
7000B/C	TC2700BK	TC1700BK	TS1700BK
8000B/C/BM/BS/BN	TC2800BK	TC1800BK	TS1800BK
8700	TC2870BK	TC1870BK	TS1870BK
9000	TC2900BK	TC1900BK	TS1900BK
E675L	TC2677BK	TC1677BK	TS1677BK
E677L	TC2677BK	TC1677BK	TS1677BK
E679L	TC2680BK	TC1680BK	TS1680BK
E680L	TC2680BK	TC1680BK	TS1680BK
W&H®			
TA96	TC2012W	TC1012W	TS1012W
TA97 C LED	TC2097WT	TC1097WT	TS1097WT
TA98	TC2011W	TC1011W	TS1011W
TA98 C LED	TC2098WT	TC1098WT	TS1098WT
TK100	TC2100WK	TC1100WK	TS1100WK
TK98	TC2098WK	TC1098WK	TS1098WK
Sirona®			
T1 Control TC3	TC2011S1	TC1011S1	TS1011S1
T2/T3 Racer	TC2011S2R	TC1011S2R	TS1011S2R
NSK®			
X600	TC2600NX	TC1600NX	TS1600NX
X600L	TC2600NX	TC1600NX	TS1600NX
X700	TC2700NX	TC1700NX	TS1700NX
X700L	TC2700NX	TC1700NX	TS1700NX
Bien-Air®			
Black Pearl	TC2011BBP	TC1011BBP	TS1011BBP
Bora	TC2011BB	TC1011BB	TS1011BB
Boralina	TC2011BB	TC1011BB	TS1011BB
Prestige	TC2011BP	TC1011BP	TS1011BP
B.A. International®			
Ultimate 675	TC2011S2R	TC1011S2R	TS1011S2R
Ultimate 685	TC2011S2R	TC1011S2R	TS1011S2R
Fona®			
6080MR	TC2011S2R	TC1011S2R	TS1011S2R
8060SR	TC2011S2R	TC1011S2R	TS1011S2R

TUBINGS SUITABLE FOR MANY UNITS

Premium Quality Silicone!



FEATURES

- For high speed handpieces, electric motors and scaler
- Premium quality silicone for extra long durability
- Available with separate air return tubing and 400° Swivel connection
- Available for the following brands: KaVo® | NSK® | Sirona® | Bien-Air® | EMS® | Acteon-Satelec® | EMS® | Chirana® | Planmeca®
- Available for the following brands: A light grey B medium grey C grey D brown

HO1014	4-hole connection without light. Open end, length: 1900 mm.
HO1016	4-hole connection with light. Open end, length: 1900 mm.
HO1026	4-hole connection with light and separate return air. Open end, length: 1900 mm.
HO1032	4-hole connection with light and separate return air. For KaVo® E-series units (except E30, E50TM, E70TM, E80TM). Length 1250 mm.
HO1031	4-hole connection with light and separate return air. For the KaVo® units 1057, 1060, 1062, 1063, 1065, 1080. Length 1350 mm.
HO1061	4-hole connection with light. For the Sirona® units A1, A2, A4, A5, AC, C1, C1+, C2, C2+, M1, M196, M1+, ProFeel, Spirit S1, S2. Length: 1370 mm.
HO1062	4-hole connection with light. For the Sirona® units C3, C3+, C6, E3. Length: 1030 mm.
HO1063	4-hole connection with light. For the Sirona® units C8+, ProFeel+. Length: 1370 mm.
HO1064	4-hole connection with light. For the Sirona® unit C8+. Length: 1370 mm.
HO1071	4-hole connection with light. For Planmeca® units. 820 Ω. Length: 1030 mm.
HO1072	4-hole connection with light. For Planmeca® units. 560 Ω. Length: 900 mm.
HO1073	4-hole Anschluss with light. For Planmeca® units. 430 Ω. Length: 930 mm.
HO2021	Suitable for EM1190K, KaVo® K190/196/200 and Chirana® CH660 electric motors. Open end, length: 1900 mm.
HO2022	Suitable for Bien-Air® MC3 (both versions) and NSK® M40 electric motors and high speed handpieces. Open end, length: 1900 mm.
HO2023	Suitable for Bien-Air® MC2 ISOLITE 300 electric motors. Open end, length: 1900 mm.
HO2026	Suitable for Bien-Air® MC2 ISOLITE 300 electric motors. 400° Swivel connection. Open end, length: 1900 mm.
HO2027	Suitable for KaVo® 700/701/702 electric motors. Open end, length: 1900 mm.
HO2031	Suitable for EM1190K, KaVo® K190/196/200 electric motors. For the KaVo® units 1058, 1062, 1063, 1065, 1066, 1080. Nut color: black, length: 1350 mm.
HO2032	Suitable for KaVo® K200 electric motors. For the KaVo® units 1058, 1062, 1063, 1065, 1066, 1080. Nut color: grey, length: 1350 mm.
HO2033	Suitable for EM1190K and KaVo® K190/196/200 electric motors. For the KaVo® units 1057, 1060. Length: 1350 mm.
HO2034	Suitable for KaVo® K192/201 electric motors. With water regulation. For the KaVo® units 1057, 1060. Length: 1350 mm.
HO2036	Suitable for EM1190K and KaVo® K190/196/200 electric motors. 400° Swivel connection. For the KaVo® units 1058, 1062, 1063, 1065, 1066, 1080. Length: 1350 mm.
HO2037	Suitable for KaVo® K700 electric motors. With water regulation and 400° Swivel connection. For the KaVo® units 1058, 1062, 1063, 1065, 1066, 1080. Length: 1350 mm.
HO2038	Suitable for KaVo® K700 electric motors. With water regulation and 400° Swivel connection. For the KaVo® units E50, E70, E80. Length: 1350 mm.
HO2040	Suitable for KaVo® K700 electric motors. With water regulation and 400° Swivel connection. For the KaVo® units 1057, 1060. Length: 1350 mm.
HO3011	Suitable for EMS® Scaler. Outer diameter 7 mm. Open end, length: 1900 mm.
HO3012	Suitable for EMS® Scaler. Outer diameter 9 mm. Open end, length: 1900 mm.
HO3013	Suitable for Bien-Air® MC3 electric motors. With water regulation. For Sirona® unit C8+. Length: 1370 mm.
HO3014	Suitable for NSK® Ti-Max M40 electric motors. For the Sirona® units A1, A2, A4, A5, AC, C1, C1+, C2, C2+, C4, C4+, E1, E2, E4, E5, EC, M1, M1+, M196, Spirit S1, S2. Length: 1370 mm.

HO3015	Suitable for Bien-Air® MC3 electric motors. With spray regulation. For the Sirona® units A1, A2, A4, A5, AC, C1, C1+, C2, C2+, C4. Length: 1370 mm.
HO3016	Suitable for Bien-Air® MC3 and NSK® Ti-Max M40 electric motors. With spray regulation and 400° Swivel connection. For the Sirona® units M1, M196, M1+, C3, C3+, C6, E3. Length: 1030 mm.
HO3017	Suitable for EM1190K, KaVo® K190/196/200 electric motors and Chirana® CH660 electric motors. For the Sirona® units A1, A2, A4, A5, AC, C1, C1+, C2, C2+, C4, C4+, E1, E2, E5, EC, M1, M1+, Spirit S1, S2. Length: 1370 mm.
HO3018	Suitable for EM1190K, KaVo® K190/196/200 electric motors and Chirana® CH660 electric motors. For the Sirona® units A1, A2, A4, A5, AC, C1, C1+, C2, C2+, C4, C4+, C5+, E1, E2, E4, E5, EC, M1, M1+, M196, Spirit S1, S2. Length: 1370 mm.
HO3019	Suitable for EM1190K, KaVo® K190/196/200 electric motors. For the Sirona® units C3, C3+, C6, E3. Length: 1030 mm.
HO3020	Suitable for Bien-Air® MC2 IR and ISOLITE 300 electric motors. With spray regulation. For the Sirona® units A1, A2, A4, A5, AC, C1, C1+, C2, C2+, C4. Length: 1370 mm.
HO3021	Suitable for Acteon-Satelec® scaler handpieces. Outer diameter 7 mm. Open end, Length: 1900 mm.
HO3022	Suitable for Acteon-Satelec® scaler handpieces. Outer diameter 9 mm. Open end, Length: 1900 mm.
HO3023	Suitable for Bien-Air® MC3 electric motors. For the Sirona® units A1, A2, A4, A5, AC, C1, C1+, C2, C2+, C4, C4+, E1, E2, E4, E5, EC, M1, M1+, ProFeel, Spirit S1, S2. Length: 1370 mm.
HO3024	Suitable for Bien-Air® MC3 electric motors. For the Sirona® units C3, C3+, C6, E3. Length: 1030 mm.
HO4011	Suitable for Bien-Air® MC3 electric motors. For Planmeca® units. 82 Ω. Length: 1000 mm.
HO4012	Suitable for Bien-Air® MC3 electric motors. Mit 400° Swivel connection. For Planmeca® units. 82 Ω. Length: 1000 mm.
HO4013	Suitable for Bien-Air® MC3 and NSK® Ti-Max M40 electric motors and high speed handpieces. For Planmeca® units. Length: 980 mm.
HO4014	Suitable for Bien-Air® MC3 and NSK® Ti-Max M40 electric motors and high speed handpieces. For Planmeca® units. 82 Ω. Length: 900 mm.
HO4015	Suitable for EM1190K, KaVo® K190/196/200 electric motors. For Planmeca® units. 270 Ω. Length: 1010 mm.
HO4017	Suitable for EM1190K, KaVo® K190/196/200 electric motors. 400° Swivel connection. For Planmeca® units. 270 Ω. Length: 1010 mm.
HO4018	Suitable for EM1190K, KaVo® K190/196/200 electric motors. 400° Swivel connection. For Planmeca® units. Length: 1000 mm.
HO4019	Suitable for EM1190K, KaVo® K190/196/200 electric motors. 400° Swivel connection. For Planmeca® units. 270 Ω. Length: 1000 mm.
HO4020	Suitable for EMS® scaler handpieces. Outer diameter 7 mm. For Planmeca® units. 1300 Ω. Length: 1030 mm.
HO4021	Suitable for EMS® scaler handpieces. Outer diameter 9 mm. For Planmeca® units. 1300 Ω. Length: 1030 mm.

Keys **RELIABLE HELPERS!**



KE1011KT	For KaVo® Super Torque/Bella Torque high speed handpieces with 2-hole back caps. With attachment for torque wrench RT2025 (1,0 Nm).
KE1022KT	For MK-dent & KaVo® high speed handpieces with standard head. With attachment for torque wrench RT2025 (0,3 Nm).
KE1023T	For MK-dent high speed handpieces with small head. With attachment for torque wrench RT2025 (1,0 Nm).
KE1500N	For NSK® TiMax X500/X500L high speed handpieces.
KE1600N	For NSK® TiMax X600/X600L high speed handpieces.
KE1700N	For NSK® TiMax X700/X700L high speed handpieces.
KE1637T	For KaVo® Mira 635/Bella Torque 637 high speed handpieces. With attachment for torque wrench RT2025 (1,0 Nm).
KE1650T	For MK-dent high speed handpieces with standard head and 3-/4-hole spray and KaVo® Super Torque/Gentle Force high speed handpieces. With attachment for torque wrench RT2025 (1,0 Nm).
KE1922T	For MK-dent PRIME LINE high speed handpieces with standard head. With attachment for torque wrench RT2025 (0,35 Nm).
KE2011BT	For low speed handpieces (SP2288 & SP1021). With attachment for torque wrench RT2026 (1,8 Nm).
KE2011T	For low speed handpieces. With attachment for torque wrench RT2025 (1,0 Nm).



BECOME A PART OF OUR GLOBAL NETWORK!



Contact us for more information.



MK-dent GmbH

Marie-Curie-Straße 2
D-22941 Bargteheide

T +49 (0) 4532 40049-0
F +49 (0) 4532 40049-10

Info@mk-dent.com
www.mk-dent.com